

Product Data

Coating for Protection of Surfaces Subject to Hot Aqueous & Hydrocarbon Immersion

Belzona® 5891 (HT Immersion Grade) is a two-component coating system for corrosion protection of metallic surfaces, against attack from aqueous solutions operating at temperatures up to 194°F (90°C).

Belzona® 5891 (HT Immersion Grade) will:

- Outperform glass flake systems
- Extend equipment life
- Cut downtime
- Protect against corrosion damage

Belzona® 5891 (HT Immersion Grade) can be spray applied and post cures in service resulting in reduced production downtime.

Belzona® 5891 HT Immersion Grade



Coalescers



Condensate Tanks



Storage Tanks



Separators

Applications for Belzona® 5891 (HT Immersion Grade) include:

- Separators
- Condensers
- Knockout drums
- Evaporators
- Strippers and scrubbers
- Condensate tanks
- Storage tanks
- Filters
- Diffusers
- Coalescers

www.belzona.com

Belzona provides the solution to your repair and maintenance needs.


BELZONA®
Repair • Protect • Improve

Belzona® 5891 (HT Immersion Grade) is:

Belzona® 5891

HT Immersion Grade

Simple

- Hand or spray applied
- Cures at ambient temperatures
- Post cures in service
- Single coat application

Safe

- Spark testable
- Solvent free

Versatile

- Suitable for continuous immersion in water, aqueous solutions, and hydrocarbons up to 194°F (90°C)
- Compatible with cathodic protection systems

Effective

- Long term corrosion protection
- Resistant to rapid depressurization
- Resistant to steam out processes



Filters

For more information, please contact your local Belzona representative.



QUALITY PRODUCTS - TECHNICAL SUPPORT

The Belzona product range is manufactured through stringent quality and environmental control guidelines complying with the internationally recognized requirements of **ISO 9001:2008** and **ISO 14001:2004**. Belzona has a global distribution network of over 140 Distributors operating in 120 countries. Local support is provided by trained Technical Consultants who will diagnose the problem, recommend the solution, and provide 24-hour on-site application supervision.

Copyright© 2008 by Belzona International, Ltd. All rights reserved. No part of this work may be reproduced or used in any form or by any means - graphic, electronic, or mechanical including photocopying, recording, taping, or information storage and retrieval systems - without written permission of Belzona International, Ltd. Belzona® is a registered trademark.

www.belzona.com



ISO 9001:2008
Q 09335
ISO 14001:2004
EMS 509612

Europe & Africa
Belzona Polymerics Ltd.
Harrogate, UK
t: +44 1423 567641
f: +44 1423 505967
e: belzona@belzona.co.uk

The Americas
Belzona Inc.
Miami, FL USA
t: +1 (305) 594-4994
f: +1 (305) 599-1140
e: belzona@belzona.com

Asia & Oceania
Belzona Asia Pacific
Chonburi, Thailand
t: +66 38 378099
f: +66 38 378098
e: belzona@belzona.cn

China
Belzona Hong Kong
Hong Kong, China
t: +852 3101 7461
f: +852 3101 7530
e: belzona@belzona.hk


BELZONA®
Repair • Protect • Improve